

# FIREFIGHTING HOSES TECHNOLEN DUPLEX D25, C42, C52, B75

základní provedení zásahových hadic DUPLEX



## DUPLEX

- basic execution of firefighting hoses DUPLEX
- unique technology T-SMART DOUBLE
- outside double Heavy Duty high-strength polyester fabric and inside EPDM rubber liner
- intended for very heavy and frequent use by firefighters and constructions
- 2x more resistant than hoses PYROTEX
- very high resistance against the abrasion and mechanical damage
- suitable for the temperatures from  $-30\text{ }^{\circ}\text{C}$  till  $+50\text{ }^{\circ}\text{C}$ , temporarily till  $+80\text{ }^{\circ}\text{C}$ .
- certificated according to ČSN 80 8711

## TECHNICAL PARAMETERS

INNER DIAMETER	WORKING PRESSURE	BURST PRESSURE
25 mm	20 bar	70 bar
42 mm	20 bar	70 bar
52 mm	20 bar	70 bar
75 mm	20 bar	70 bar

\* data apply to hoses without couplings

## INTERESTED IN THIS HOSE?

We will be glad to prepare a quotation, recommend a suitable design and answer your technical questions.

Luděk Klusáček

Phone: +420 602 631 844

E-mail: [export@technolenbojanov.cz](mailto:export@technolenbojanov.cz)

Web: [www.technolen.cz](http://www.technolen.cz)